

Coat "Fiona"

Model 6610

Sizes 36–48



PRINT THE CUT

1. Open the pattern PDF and set the control square to Page 1 with the setting "Original size" on DIN Print A4 paper (do not click on "Adjustment to page size"!)
2. Check the square – if it is 10x10 cm, print out the whole cut sheet.
3. Put all pages together as shown in the overview and attach them to the boundary lines row by row. Then glue the rows together.
4. Compare the body measurements with the table measurements and cut out the cut parts in the appropriate size (the overview of the cut parts is on the pattern sheet). **Important:** Instructions do not include seam allowances, unless otherwise indicated.

SUPPLIES

- 2.6–3.4 m "Monte Rosa" woollen fabric, 140 cm wide
- 2.3–3.1 m lining fabric, 140 cm wide
- Shoulder pads, if wished
- Hanging ribbon
- Vilene
- 2 buttons, diameter 28 mm (Union Knopf)
- 3 press studs, diameter 25 mm (Union Knopf)
- BERNINA sewing machine
- Walking foot or Dual Feed for sewing on button

CUTTING OUT

- 2 × front
- 2 × front facing
- 2 × top back section
- 2 × bottom back section
- 2 × sleeve
- 1 × upper collar to fabric fold
- 1 × under-collar to fabric fold
- 2 × flap: Sizes 36/38, 16 cm long; sizes 40/42, 16.5 cm; sizes 44–48, 17 cm; all 7 cm wide, finished width 3.5 cm.

CUTTING OUT LINING

4 × pocket bag
Paper pattern: Cut off front piece along the facing line; cut out 2 × outer front section. Combine pieces top and bottom back section into one pattern piece and cut out with a pleat of approx. 2 cm in the centre-back. Cut out sleeve as for outer fabric.

We recommend a 4 cm seam allowance on the outer fabric and 2 cm on the lining.



made to create **BERNINA**

Coat "Fiona"

Model 6610

Sizes 36-48



INSTRUCTIONS

1. Iron Vilene onto facings, under-collar, flaps, pocket openings, hem and sleeve hems. Let cool thoroughly.
2. Sew flap pockets (see also: "Tips" in [Inspiration 64](#)). Fold flap in half lengthways with right sides facing; sew sides closed, turn flap right-side-out and topstitch. Pin flap with open edges to the side of the pocket opening facing the centre-front; pin pocket bag right-sides-facing to the other side. Sew on flap. Sew on pocket bag so that the seam ends are later covered by the flap. The seam will then be 2-3 stitches shorter on each side. Sew second pocket bag right-sides-facing over the flap. Snip pocket opening from the wrong side of the fabric. About 1 cm before the end, cut diagonally into the corners without damaging the sewing threads and without cutting into the pocket bags. Pull pocket bags to the inside and pin. Topstitch flap join seam. Fold pocket bags to centre-front and close, including the little triangles created when snipping into the corners. Trim and grade seam allowances. Place flap over pocket slit. Edgestitch on short sides of flap from the right side.
3. Close all darts on top-back, front and sleeve. Close centre-back seams, sewing only up to the slit marking on the bottom back section, then crossways over the slit facing. Close back cross seam. Press seam allowances and facings into the left back section. Close side seams and shoulder seams.
4. Close sleeve seam, gather sleeve head and insert sleeve. Sew in shoulder pads if wished.
5. Stitch under-collar to neckline of coat, leaving the seam allowances open at the ends. Snip seam allowance of facings in the corners up to the seam line.
6. Complete the lining except for the shoulder seam. Sew lining right-sides-together to facings and close shoulder seam. Pin hanging loop into centre-back of lining. Sew upper collar to front facings and back lining, leaving the seam allowances open at the ends; snip corners.
7. With right sides facing, stitch together and turn front edges of coat and facings and collar sections. Stitch together collar seam allowances along the neckline. With right sides facing, stitch together sleeve hems of lining and outer fabric; turn right-side-out. Secure seam allowances of outer fabric and lining at the shoulder and under the arm.
8. Hem lining and coat. Sew lining to slit: Place lining and outer fabric together with wrong sides facing. Pin slit ends together, shifting the lining 1 cm upwards. Sew long edge of lining to underlap. Snip lining crossways below the slit marking far enough so that the long edges of the lining and coat overlay can be stitched together and turned. Sew on lining. Turn under top seam allowance of lining and sew on by hand if necessary. Diagonally topstitch slit through all the layers from the right side.
9. Work buttonholes, using the walking foot or Dual Feed. Sew on buttons and press studs. Stitch together outer fabric and lining crossways to the front edge along the overlay between the press studs for a few centimetres.

