

Short jumpsuit "Nele"

Model 6560
Sizes 36-44



PRINT THE CUT

1. Open the pattern PDF and set the control square to Page 1 with the setting "Original size" on DIN Print A4 paper (US-Letter) (do not click on "Adjustment to page size"!)
2. Check the square – if it is 10x10 cm, print out the whole cut sheet.
3. Place all pages next to each other as indicated by the arrows and adhere them row by row along the boundary lines, then glue the rows together.
4. Compare the body measurements with the table measurements and cut out the cut parts in the appropriate size (the overview of the cut parts is on the pattern sheet). **Important:** Instructions do not include seam allowances, unless otherwise indicated.

SUPPLIES

- 1.0–1.2 m jersey knit, 130 cm wide
- Jersey remnants in green and yellow
- 1.3–1.5 m cord
- 2 cord stops
- Elastic, 1 cm wide
- BERNINA overlocker
- BERNINA coverstitch machine
- BERNINA sewing machine
- [Edgestitch foot no. 10](#)
- Dual Feed or [Walking foot no. 50](#)

CUTTING OUT

- 1 2 x front
- 2 2 x back
- 3 1 x facing to fabric fold

Binding 30x3.5 cm, finished width 0.8 cm.

Cord casing 93 to 107x3 cm, finished width 1.5 cm.

Straps: 6 strips approx. 70x1.5 cm, finished strap length 60 cm.

INSTRUCTIONS

1. Place front and back sections right-sides-together in each case and close centre-front and centre-back seams. Close side seams and crutch seam.
2. Bind front neckline with binding, sewing right side of binding to wrong side of neckline. Place binding around the edge, turn under seam allowance and stitch on.
3. Stitch facing right-sides-together to top edge. Narrow-edgestitch top edge of facing with the coverstitch machine or the edgestitch foot (sewing machine). Sew on bottom edge of facing in the same manner. Depending on its "give", cut elastic around 5–10 cm shorter than the length of the facing. Pull through elastic. Secure ends on short edges of facings and stitch through vertically from the right side.
4. Iron under seam allowances of casing. Pin casing to centre of marking in pattern; on each side, casing begins 1.5 cm from centre-front seam. Edgestitch casing on, pull through cord and attach cord stops.
5. Hem trousers with the coverstitch machine. Place three jersey strips at a time one on top of the other and sew together at the beginning for approx. 2 cm. Plait straps and knot ends. Place beginning of strap under front neckline corner and stitch on in the ditch of the straight-stitched seams.



made to create **BERNINA**