

Skirt "Selina"

Model 121-15

Size 36-48



PRINT THE CUT

1. Open the pattern PDF and set the control square to Page 1 with the setting "Original size" on DIN Print A4 paper (US-Letter). (Do not click on "Adjustment to page size"!))
2. Check the square – if it is 10×10 cm, print out the whole cut sheet.
3. Place all pages next to each other as indicated by the arrows and adhere them row by row along the boundary lines, then glue the rows together.
4. Compare the body measurements with the table measurements and cut out the cut parts in the appropriate size. (The overview of the cut parts is on the pattern sheet.)

Important: Instructions do not include seam allowances, unless otherwise indicated!

SUPPLIES

- 1.6–1.7 m rayon print fabric, 140 cm wide
- 1 zip, 22 cm
- Fabric lining G 785 or G 710
- Edge tape

OPTIONAL BERNINA ACCESSORIES

- [Zipper Foot #35](#)
- Dual Feed or [Walking Foot #50](#)

CUTTING

- 1 2× front yoke on the fold
- 2 1× front part on the fold
- 3 2× rear yoke on the fold
- 4 1× back part on the fold

INSTRUCTIONS

1. In the area of the zip iron edge tape on all parts. Iron fabric lining on the inner yoke parts and let them cool off thoroughly.
2. Sew the outer yokes right side on right side on the skirt parts. Close the right side seam completely and the left side seam beneath the slit marking. Sew in the zip with Foot #35.
3. Close the right side seam of the inner yoke. Pin the upper edges of the yoke right side on right side on top of each other. In doing so, fold the allowances of the inner yoke approx. 1 cm in front of the zip wrong side on wrong side. Place the zip including the allowance wrong side on wrong side on top of it. Sew the long edges of the yoke and the zip together. Close the upper edges and turn it over. Also refer to the **tips** in Inspiration 75. Sew on the inner yoke edge from the right in the seam shadow. Hem the skirt.



made to create **BERNINA**