

Short "Rieke"

Model 6221

Sizes 36-48



PRINT THE CUT

1. Open the pattern PDF and set the control square to Page 1 with the setting "Original size" on DIN Print A4 paper (US-Letter) (do not click on "Adjustment to page size"!)
2. Check the square – if it is 10x 10 cm, print out the whole cut sheet.
3. Place all pages next to each other as indicated by the arrows and adhere them row by row along the boundary lines, then glue the rows together.
4. Compare the body measurements with the table measurements and cut out the cut parts in the appropriate size (the overview of the cut parts is on the pattern sheet). **Important:** Instructions do not include seam allowances, unless otherwise indicated.

SUPPLIES

- 1.1 – 1.2 m viscose print, 135 cm wide
- Fabric remnant
- Interfacing
- In-seam zip, 22 cm long
- BERNINA sewing machine
- BERNINA overlocker
- [Zipper foot no. 35](#)

CUTTING OUT

- 1 2 x front
- 2 2 x front waistband
- 3 2 x pocket bag
- 4 2 x back
- 5 2 x back waistband

0.9 – 1.1 m bias binding from fabric for top, 1 cm wide, finished width 0.5 cm.

INSTRUCTIONS

1. Close darts. Close right side seam above and below pocket opening, continuing to sew with a long straight-stitch as a basting stitch at the pocket opening. Sew pocket bags right-sides-facing to seam allowance, leaving 1 cm free at the top and bottom. Press pocket bags into front section and close. Unpick basting stitch.
2. Close inside leg seams and crutch seam. Place pleat markings (those with the cross-mark at the bottom) together with right sides facing and sew 6 cm as marked. Fold pleats towards the centre-front and secure along the top edge.
3. Iron interfacing onto waistband sections and let cool thoroughly. With right sides facing, stitch front and back waistband sections together along the top edges and turn; close right side seam. Fold bias binding in half lengthways and press. Sew binding to top edge of shorts. Stitch outer waistband right-sides-facing to top edge.
4. Insert zip into left side seam. Close remainder of side seam. Secure zip ends to seam allowance. Stitch waistband right-sides-facing to zip. Neaten inner waistband with the overlocker and stitch in the ditch from the outside. Hem shorts.

