

STUDIO COSTURA patterns



HANNA BRALETTE

sewing pattern


A delicate lace bralette that combines both beauty and comfort

size XS - XL

WWW.STUDIOCOSTURA.COM

DESCRIPTION

Hanna is a soft cup bralette made with stretch lace and underlined with knit fabric. The neckline has a beautiful scalloped edge lace detail and all the seams are neatly finished both on the outside and the inside. Using stretch fabrics makes this pattern easy to fit and it's comfortable for everyday use but looks fancy enough for a special occasion as well.



FRONT

BACK

SUPPLIES

stretch lace (at least 16 cm (6 1/3 in) wide)	2 m (2 1/5 yd)
knit fabric for lining (120 cm (1 1/3 yd) wide)	0.25 m (1/3 yd)
10 mm (3/8 in) plush back elastic	2 m (2 1/5 yd)
10 mm (3/8 in) strap elastic	0.7 m (3/4 yd)
narrow clear elastic	0.7 m (3/4 yd)
10 mm (3/8 in) rings & sliders	2 of each
2 row hook & eye set	1 set

Fabric suggestions

Lace

This pattern is designed for stretch laces, make sure that the lace has horizontal stretch in it.

Lining fabric

You can use different types of knit fabrics for the lining of the bralette, the results will vary slightly according to the knit you choose. The fabric should stretch in both directions, aprox 60% of stretch in one of the directions is perfect. Look for lightweight knit fabrics with spandex in them for the best fit: cotton/viscose jersey, lycra, polyester etc knits.

Other supplies

- washable fabric marker
- stretch needle
- polyester thread

You can also use mesh to line the bralette, it will give a more transparent result.

MEASUREMENTS

This pattern is designed for knit fabrics which means that the bralette fits well to a variety of bust sizes, however it is most comfortable for bra cup sizes A-C (as there are no underwires this bralette is not as supportive as a proper full band bra, however every woman has their own fit and comfort preferences).

To know your size you have to measure the circumference of the fullest part of your bust. Pick a size from the chart according to that measurement. As the fit of the bralette will be very different according to every person and their unique breast shape and underbust circumference I highly suggest you to **make a quick muslin** before cutting into your beautiful lace. See page 4 for a fitting guide.



SIZE CHART

Metric (centimeters)					
Size	XS	S	M	L	XL
Full bust (cm)	86-90	91-95	96-100	101-105	106-110

Imperial (inches)					
Size	XS	S	M	L	XL
Full bust (in)	34-35	36-37	38-39	40-41	42-43

PATTERN PIECES

- A** inner cup (cut two from lace)
- B** outer cup (cut two from lace & two from lining)
- C** band (cut two from lace & two from lining)
- D** inner cup lining (cut two from lining)



PRINTING INSTRUCTIONS


Use a pdf viewer to open and print the pattern. Make sure that your printer scaling is turned off and is set up to **print at 100%**. Print page 1 of your pattern first and measure the test square to ensure accurate printing.

There are four pages in total. The pattern piece A has to be taped together, the rest of the pieces fit on individual pages.

CUTTING INSTRUCTIONS

Cut the lining pieces from the knit fabric following the greatest stretch direction on your fabric. As you need two of each pattern piece you can cut them directly with the fabric folded.

Cut the lace pieces according to the instructions on the page 5.



All seam allowances are 0.6 cm (1/4 in)

FITTING GUIDE

As explained before you should measure your bust (at the fullest part) and pick a size from the size chart according to that measurement. The bra sizing actually combines two volumes: the size of your bra cup and the size of your underbust measurement. In an ideal world these two measurements are proportional and that's how the sizing is made. The reality is that every body is different and bra sizes vary a lot, the most normal thing to happen is that your actual size will be somewhere in between the two sizes of this bralette.

The good news is that it's not a mystery at all: making a quick muslin is the easiest way to know your exact size. This extra step will save you a lot of time later on, trust me!

To try out the general fit of the bralette cut the pieces A, B and C out of a knit fabric and machine baste them together (no need to sew on the elastics). Attach the closure and sew the strap elastics in place. Try on the muslin to see the general fit. The bralette should fit closely (you don't have the elastics sewn on yet but it should still be close fitting), if it's not your case, see the following instructions.

Most common problems and how to solve them:

- *the band feels too tight and the cups seem to flatten the breast tissue*

The size you picked is overall too small, go up a size and try it out again.

- *the band feels too loose (you can easily pull it apart from your body, it's not snug) and the cups have wrinkles on them*

The size you picked is overall too large, go down a size and try out again.

- *the cups look good but the band is too loose*

Cut the cup pieces A and B in the size you used but go down one size on the band piece C. This should make the band smaller but you'll still have the same fit on the cups.

-- *the cups look good but the band is too tight*


Cut the cup pieces A and B in the size you used but go up one size on the band piece C. This should make the band bigger but you'll still have the same fit on the cups.

- *the band fits good but the cups seem to flatten your breast tissue*

Go up a size on the cup pieces A and B, but cut the same size on the band piece C. This will give your breast tissue the extra room that it's lacking at the moment.

- *the band fits good but the cups have wrinkles on the cup seams and looks like there's some extra room there*

Go down a size on the cup pieces A and B, but cut the same size on the band piece C. This will make the cup pieces smaller and they will fit your breast tissue better.



Once you know which pieces you are going to use there might be differences on the pattern pieces when you'll sew them together.


To make everything match up perfectly you have to overlap the outer cup piece B and the band piece C by 12 mm (6 mm of both of the seam allowances included in the pattern pieces). Now redraw the upper seamline to make the pieces measure the same.

(In the example I've matched up a size M cup with size S band and then I've smoothened out the seam line on the upper part of those pieces.)

Fitting a bra/bralette is a process and it's normal to take some time to get the perfect fit, don't feel overwhelmed! The materials also play a big role here: no two knits have the same stretch so they can give very different results.

CUTTING INSTRUCTIONS


1.



From lace:

Cut out the pattern pieces from lace starting with the first piece, inner cup (A). Put a single layer of lace with the **right side up** on your cutting table. The long straight edge of the pattern has to be lined up with the scalloped edge of the lace. Align the pattern piece with the **lower** part of the scallops (the scalloped edge extends from the straight edge of the pattern piece) putting the notch on the piece where one of the scallops of the lace starts. This ensures that once the central seam is sewn you'll have a beautiful scallop starting just in the middle of the neckline.

2.



You now need to cut out the second piece of the inner cup (A) and the best way to do it is to use the first lace piece you just cut out as a guide. Flip the first piece over (with the wrong side up) to be able to cut out the other piece (that way you'll have the pieces **with right sides together** when cutting) and find the exact location where the pieces align the same way on your lace (normally it means that you cut one piece on one edge of the lace and the other one on the other edge).

3.



The outer cup piece (B) and the band piece (C) can be cut out ignoring the scalloped edge, you can either fold the lace and cut them out directly in pairs or try to match the lace pattern on both again by aligning the pieces. Align the pieces on the lace according to the horizontal "greatest stretch" line (usually the stretch goes in the horizontal direction on stretch lace).

Don't forget to mark the notches with a washable fabric marker!

4.




Now you have all the lace pieces cut out and the order of the pieces goes like that: the band (C), the outer cup (B) and the inner cup (A).

From lining:

Cut out the band piece (C), the outer cup piece (B) and the inner cup lining piece (D) from the knit fabric according to the "greatest stretch" line on the pattern pieces (see page 3 for the lining cutting layout). Mark the notches on lining with a washable fabric marker.

SEWING INSTRUCTIONS

1.



On the inner cup lace piece stabilize the scalloped lace edge with clear elastic. Using a narrow zig-zag stitch (the size depends on the width of the elastic, but 3 width, 2 length zig-zag should be fine), sew over the clear elastic on the **wrong side** of the inner cup piece. You should align the elastic with the edge just where the scalloped edge starts. Hold the clear elastic with tension but don't pull it when you sew, it's there just to stabilize this edge and there shouldn't be any gathers.

2.



This is how the clear elastic should look like after sewing it on the wrong side of the inner cup piece.

TIP: using the clear elastic is a good way to stabilize lace edges and make them more durable as it's transparent and doesn't show. If you wish more support you can use a narrow plush back elastic the same way but you will see it on the right side of the lace. You can also skip the elastic in this part of the bralette on smaller bust sizes as there's normally no need for the extra support.

3.



Overlock/zig-zag (3 width, 3 length) stitch the outer edge (only the curve) of the lining piece (D).

TIP: if you want a very neat finish you could cover that edge with FOE or make a bias binding from same lining or similar light fabric.

4.



With **right sides together**, pin the inner cup lace pieces (A) together at the center seam. Overlock or zig-zag stitch (small zig-zag stitch 2 width, 3 length) the seam.

Repeat the same step for inner cup lining pieces (D).

All seam allowances are 0.6 cm (1/4 in)

5.



Hide the overlocker threads inside the seam passing them through the stitching with an embroidery needle both on the lace and knit lining pieces. If using zig-zag stitch just finish your seams with some reverse stitching and cut the threads.

To make this seam extra strong you can sew a bartack (several rows of small stitches) on the upper part of the seam on the right side to secure the stitches in place.

6.



Now let's sew together the bust seam. To have a completely neat finish both on the outside and the inside you need to put the pieces on top of each other in correct order:

1. outer cup lining piece (B) with right side up
2. inner cup lining piece (D) with wrong side up (this piece is already sewn together with the other lining piece in the previous step)
3. inner cup lace piece (A) with the right side up (this piece is already sewn together with the other lace piece in the previous step)
4. outer cup lace piece (B) with the wrong side up

7.



Pin all the four layers together on that seam matching the notches on all four pieces. It helps to first pin together the notches, then beginning and the end of the seam and then add more pins over the curves.

Overlock or zig-zag stitch (small zig-zag stitch 2 width, 3 length) the cup seam.

TIP: removing pins while sewing this small curved seam on all four layers might be a bit complicated, basting this seam together first can be very helpful

8.



Now you have a neat seam on both sides of your bralette and it should look like this. Repeat the same step for the other cup.

All seam allowances are 0.6 cm (1/4 in)

9.



Once the both sides are sewn together this is how the inside of the bralette should look like.

10.




Topstitch the cup seam from the right side using a 2.5 length straight stitch (sewing through both layers). Make sure you have the lining underneath flat in order to not create any wrinkles.

11.



On the inside pin the inner cup lining piece (D) in place on top of the inner cup lace piece (A). Make sure the center seams on both these pieces match.

12.



Using a zig-zag stitch (2.5 width, 2.5 length) sew over the finished edge of the inner cup lining piece (D) to attach the lining to the lace.

All seam allowances are 0.6 cm (1/4 in)



It's time to attach the band pieces (C) and it's done in a similar way as sewing the cup pieces together before. Place the pieces on top of each other in this order:

1. band lining piece (C) with right side up
2. lace outer cup piece (B) with right side up (already together with its lining piece (B) underneath)
3. lace band piece (C) with wrong side up

Basically you are sandwiching the outer cup pieces between the band pieces.




Overlock or zig-zag stitch (small zig-zag stitch 2 width, 3 length) the seam. Repeat with the other side. Now you have all the pieces together and it looks like a bralette!

TIP: I usually don't topstitch this seam as we did on the cup seam but you can do it if you wish.



It's time to sew on the elastic on the lower part of the bralette. With the **right side of the bralette up**, put the elastic with the decorative edge towards the inside of the bralette (left side) and with the plush side up. Put it on the edge of the band on the lower part of the bralette.




Using a zig-zag stitch (2.5 width, 2.5 length) **sew close to the decorative edge of the elastic** while pulling it slightly to give it some tension. Sew all the way to the other end of the band.

TIP: The lingerie elastics are different, some are "softer" and others are "stronger", the amount you should be pulling when sewing depends on that a lot. Think that the bralette is already designed to be snug and the elastics just need to give the final touch. You need to find the way to sew the elastic with right tension: don't leave it too "loose" but don't gather the fabric with elastic either. It takes a little practice but it's not so hard!

For more tips and tricks on sewing lingerie elastics visit the Hanna bralette sewalong over at www.studiocostura.com



Turn your bralette with the wrong side up and cut away the fabric that extends the zig-zag stitch. This step reduces bulk in this area and once you turn the elastic under everything will be neat with no fabric edges showing.




Prepare the straps:

- cut two pieces of strap elastic 35 cm (13 in) long each
- with the right side of the elastic facing you, pass the elastic through the slider
- on the wrong side of the elastic fold 1 cm (3/8 in) down. Stitch with a straight stitch (2 length) back and forth a couple of times to secure the end of the strap
- with the elastic **wrong side up** pass the ring through the other end
- fold the end of the elastic back and pass it through the slider as you did in the first step



We'll be using the second row of zig-zag stitch on the band elastic to secure the strap in place. Place the strap elastic with **wrong side up** where the notch on the band piece (C) marks the strap position. Do it on both sides of the band.



Flip the elastic to the wrong side of the bralette and using a zig-zag stitch (2.5 width, 2.5 length) sew the second row of stitching **close to the non decorative edge of the elastic**.

As you already have the elastic stretched from the first pass you don't need to worry about it now. Just make sure that both elastic and the fabric are evenly fed through your machine. You can stretch both of them lightly to make sure there won't be any wrinkles when you sew.

24.



This is how the band elastic should look like after the two rows of zig-zag stitch on it and with the strap elastic in it's place.

25.



Before attaching the elastic in the underarm area check if your closure fits properly with the end of the band. You should have the fabric on the band piece extending **exactly the width of your elastic** at that point as this is the amount of fabric that will be folded under after sewing on the elastic. If your closure is smaller you can just cut away a bit of fabric to make them match.

TIP: you can use closures with various widths when you make sure that they fit with the pattern. The end of the band piece should have the width of your closure + two times the elastic width. If necessary draw a new line on the pattern piece marking your desired width on the band and gradually join this point with the rest of the pattern piece.

26.




Sew the elastic in the underarm and band pieces the same way you did before. Start on the right side of the bralette on the first row of zig-zag stitch, cut away the extra fabric under the elastic and fold it on the other side and do the second row of stitching. **Don't sew over the strap elastic**, leave it out because we'll be attaching it on the next step.

27




Using a straight stitch (2 length) sew the strap elastic in place over the elastic you just sewed on the upper part of the band piece **on the inside of the bralette**. You can sew a double row of back and forth stitches to make it extra secure.

28.



Making sure that the strap elastic is not twisted, pull the lace end of the inner cup piece (A) through the ring attached to your elastic for about 1.5 cm (2/3 in). Secure it in place with some rows of straight stitching (2 length) on the wrong side of the bralette.


29.



The eyes of the closure go on the right band piece and the hooks on the left band piece when you have your bralette with the right side up. (Remember that the eyes will be seen on the right side of the bralette and the hooks will be seen on the wrong side of the bralette.)

Open the little pocket of the closure and slip the band piece inside it. Sew a double row of straight stitching (2.5 length) to join them.

30.



The hooks are sewn **on the wrong side** of the bralette to prevent the machine being damaged with the metal parts. Again, slip the band piece inside the closure and sew one row of straight stitching (2.5 length) to join them.

TIP: there's not so much room to do the stitching as the hooks are on the way of your sewing machines presser foot. You can either use a narrower foot, move the needle position away from the hooks to be able to sew more on the border or you can try the zipper foot to help you at that point

*When sewing on a closure with raw edges, pass a narrow zig-zag stitch (3 width, 1 length) over the edges.

31.



That's it, you have successfully sewn a lace bralette. Congratulations!

Share your work on Instagram with #hannabralette and tag @studiocostura so I can see your makes!